

Job Name:	
Type:	
Part #:	
Notes:	

ELEDEXCU

All LED Exit & Emergency Thermoplastic Combo

















Illumination

- · Long lasting, efficient ultra bright white LED lamp heads.
- 1.0 watt (8 LEDs x 0.125W) per head.
- High performance chrome-plated metallized reflector and plastic lens for optimal light distribution.
- Adjustable LED lamp heads provides optimal center-to-center
- Long life, energy efficient Red or Green LED EXIT sign illumination.

Electrical

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 9.6V Long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

Options

- RC: Remote capacity of up to 3.0 watts.
- HL: 12-LED heads provide increased center-to-center spacing (1.5W per head).
- NH: No lamp head attach to the unit enabling it to be used as remote capable exit sign.
- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- Custom: Signs available with requested "special" wording.

Ordering Information

*Special voltage & SALIDA face plate options available.




Housing

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- EZ snap-out Chevron directional indicators.

Warranty/Listing

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C -40°C).
- Certified to CEC under Title 20 Regulations.

Dimensions



Product Number: ELEDEXCU	NF:	LC:	HC:	0:

	Model	No. of Face		Letter Color		Housing Color		Options	
1	ELEDEXCU	2	Universal	R	Red	W	White	RC	Remote Capacity
			Single/Double Face	G	Green	В	Black	HL	High Lumen No
			lace					NH	Lamp Heads
								SDT	Self-Diagnostics
								CUSTOM	Custom Wording

Office: 215-512-7000 • Fax: 267-288-5604

www.EnvoyLighting.com

08 2019