



DRILLED PER FIXTURE REQUIREMENTS:  
 D1- DRILLED FOR 1 FIXTURE  
 D2- DRILLED FOR 2 FIXTURES AT 90° OR 180°  
 D3- DRILLED FOR 3 FIXTURES  
 D4- DRILLED FOR 4 FIXTURES

5/16-18 UNC RIVET NUT  
 4 PLACES @ 90°

Ø.44 ~ THRU  
 FOR 3/8-16 UNC THRU BOLT

TENON CENTERING COLLAR  
 FOR Ø2.38 OD TENON

.25  
 .50-50  
 (4)

REMOVABLE CAP

4.00 SQ X 11. GA TUBE

FINISH: BRACKET TO BE STANDARD POLYESTER POWDER COAT FINISH.

SOME GEOGRAPHICAL AREAS HAVE SPECIAL WIND CONDITIONS THAT CAN CREATE WIND INDUCED VIBRATIONS CAUSING A FATIGUE PROBLEM. NO METHOD HAS YET BEEN FOUND FOR PREVENTING OR REDUCING DESTRUCTIVE LIGHTNING STRIKE CONTACTS. CONTACT LOCAL ENGINEER. CANNOT BE GUARANTEED AGAINST, AND ARE THE RESPONSIBILITY OF A LOCAL SITE ENGINEER.	
TITLE:	
CATALOG:	
DWG NO:	PTTA-4SQ
SIZE:	C
SHEET 1 OF 1	

DRAWN: M. HARVALA	12/3/2009
CHECKED:	DATE:
REVISION:	APPROVED:
APPROVED:	QUOTE:
S.O.#	SCALE: NONE
REF:	

