

**3-Wattages + 3-CCT (30/40/50K), Wet Rated, 130 lm/W, Dimmable + Smart**

## FEATURES

<b>Lumen Output</b>	5200 to 15600 lumens
<b>Efficacy</b>	130 lm/W
<b>Input Voltage</b>	120-277V
<b>Dimmable</b>	0-10V Continuous
<b>CCT</b>	Select (3000K, 4000K, 5000K)
<b>Rating</b>	Wet Location
<b>Warranty</b>	5 Years

## APPLICATIONS

Premium outdoor luminaire suitable for wall mounting on building exteriors for entrances, courtyards, alleys, and pedestrian walkways.

## CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

## ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3000K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 113°F (-20°C to 45°C).

## MOUNTING

Wall mounted installations. Includes Liquid Level inside housing.

## OPTICS

Anti-UV Prismatic Tempered Glass Lens, or Anti-UV Prismatic Polycarbonate Lens available.

## CONTROLS

Installed fixture integrated Photocell sensor available. Installed fixture integrated PIR Sensor with Daylight Priority available. Remote Control available.

## EMERGENCY

Installed 90 Minute Emergency Backup Battery LED Driver available.

## LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

## WARRANTY

5 year exclusive limited warranty.

Project:
Date:
Catalog No:
Prepared By:

80W Max and 120W Max Models



\*Includes Liquid Level and Silicone Water Repellent Ring



PIR Sensor



Remote Control




Emergency Driver



## TUNABLE CORRELATED COLOR TEMPERATURES (CCT)


3000K



4000K



5000K



## SPECIFICATIONS

### ENERGY DATA

**Input Voltage:** 120-277V  
**Input Frequency:** 50/60 Hz  
**Wattage:** 3-Wattages (80W Max, 120W Max)  
**Power Factor:** >0.9  
**Total Harmonic Distortion (THD):** <15%  
**Operating Temperature:** -4°F to 113°F (-20°C to 45°C)

### LIGHTING DATA

**Lumens:** 5200 to 15600  
**Lumens Per Watt:** 130 lm/W  
**Correlated Color Temperature (CCT):** 3-CCT (30K, 40K, 50K)  
**Dimmable:** 0-10V  
**Color Rendering Index (CRI):** >70  
**L70:** 50000 hours

## ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
EWK0408-80/60/40W-H-TCP(XX) *Glass Lens	40W	120-277V	0.37A@120V, 0.16A@277V	5200	130 lm/W	(3000K,	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
	60W		0.55A@120V, 0.24A@277V	7800		4000K,			
	80W		0.73A@120V, 0.32A@277V	10400		5000K)			
EWK0408-80/60/40W-H-TCP(XX) *PC Lens	40W	120-277V	0.37A@120V, 0.16A@277V	5200	130 lm/W	(3000K,	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
	60W		0.55A@120V, 0.24A@277V	7800		4000K,			
	80W		0.73A@120V, 0.32A@277V	10400		5000K)			
EWK0412-120/100/90W-H-TP(XX) *Glass Lens	90W	120-277V	0.83A@120V, 0.36A@277V	11700	130 lm/W	(3000K,	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
	100W		0.92A@120V, 0.40A@277V	13000		4000K,			
	120W		1.10A@120V, 0.48A@277V	15600		5000K)			
EWK0412-120/100/90W-H-TP(XX) *PC Lens	90W	120-277V	0.83A@120V, 0.36A@277V	11700	130 lm/W	(3000K,	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
	100W		0.92A@120V, 0.40A@277V	13000		4000K,			
	120W		1.10A@120V, 0.48A@277V	15600		5000K)			

### Control

**BRI823-X-D** [INSTALLED] 120-277V Fixture Mounted PIR Bi-Level Daylight Outdoor Smart Sensor with Arm

**RC-100** Sensor Remote Control (ANT and BRI Series)

**SD250** [INSTALLED] Step-Down Autotransformer 480V to 277V, Up To 250W

### Emergency

**EM20 (BLD-CM20H-YYY)** [INSTALLED] Emergency Backup LED Driver, 20W, 90-Min Battery

## PHYSICAL DIMENSIONS

### All Models

14.21"L x 9.27"W x 7.31"D

